



Polyester Protective Tape

1675

Technical Data

August, 2004

Product Description 3M™ Polyester Protective Tape 1675 is a polyester tape with a high temperature resistant low-tack adhesive system for temporary surface protection.

Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester film	Acrylic	Clear	48 in. (1200 mm) x 1000 ft. (304.8 m)

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	2 oz./in. width (2 N/100 mm) nominal	D-3330
Tensile Strength: (Break)	24 lbs./in. width (420 N/100 mm)	D-3759
Elongation: (Break)	88%	D-3759
Total Tape Thickness:	1.3 mils (0.03 mm) nominal	D-3652
Service Temperature:	350°F (177°C) maximum	

Features

- Low-tack adhesive removes cleanly after exposure to temperatures up to 350°F (177°C) and is non-staining/non-corrosive which helps eliminate the need to rework parts.
- Transparent backing allows visual inspection without tape removal.
- Abrasion resistant backing prevents tearing that can occur during the forming process.

Application Ideas

- Substrates where temperatures up to 350°F (177°C) are present.
- High-pressure plastic laminates during thermo-forming.
- Plastics – gloss high-pressure laminates.

General Information

- Ideal for the protection of high-pressure laminates during thermo-forming process. Performance is enhanced by clean surfaces prior to tape application. For optimum performance, this tape should be applied and removed at a temperature not less than 60°F (16°C).
- Polyester film offers good optical clarity and heat resistance.

3M™ Polyester Protective Tape

1675

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within 12 months from date of manufacture.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-241-2031 or 828-465-3053. Address correspondence to: 3M/PolyMask, 500 Thornburg Dr., P.O. Box 309, Conover, NC 28613. Our fax number is 1-800-672-3038 or 828-465-2404.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that PolyMask Corporation and 3M believe are reliable. However, many factors beyond the control of PolyMask Corporation and 3M can affect the use and performance of a PolyMask Corporation product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the PolyMask Corporation product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in other product literature, packaging inserts or product packaging for individual products, PolyMask Corporation warrants that each PolyMask Corporation product meets the applicable specifications at the time PolyMask Corporation ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **POLYMASK CORPORATION AND 3M COMPANY MAKE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the PolyMask Corporation product is fit for a particular purpose and suitable for user's application. If the PolyMask Corporation product is defective within the warranty period, your exclusive remedy and PolyMask Corporation's sole obligation will be, at PolyMask Corporation's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M Company and PolyMask Corporation will not be liable for any loss or damage arising from the PolyMask Corporation product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This product was manufactured under a quality system registered to ISO 9001:2000 standards by PolyMask Corporation, a joint venture of 3M and Sealed Air Corporation, and is sold by PolyMask Corporation with 3M acting as the sales representative of PolyMask Corporation.



**Industrial Business
Industrial Adhesives and Tapes Division**

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
www.3M.com/protectivetapes



*Recycled Paper
40% pre-consumer
10% post-consumer*

"3M" is a trademark of 3M Company used under license by PolyMask Corporation. Printed in U.S.A.
©3M 2004 70-0707-7602-9 (8/04)